

Model: AH4540X-TZ1C
Product Description

Type:	Reciprocating Compressors
Application:	HBP - High Back Pressure
Refrigerant:	MULTI
Voltage/Frequency:	440V 3~ 60Hz 400V 3~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	0
Weight Unit of Measure:	
Displacement (cc):	74.25
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	1480

Electrical

Voltage Range (50 Hz):	
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	46
Rated Load Amps (RLA 50 Hz):	7.5
Rated Load Amps (RLA 60 Hz):	7.7
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	3.29
Motor Resistance (Ohm) - Start:	

MotorType:
Overload Type:

3PH

Relay Type:

[Agency Approval](#)