

**Model: AJ2433X-FZ3B**
**Product Description**

**Type:** Reciprocating Compressors  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** MULTI  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					

**General**

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 22  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 26.15  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 475

**Electrical**

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):**  
**Locked Rotor Amps (LRA):** 30  
**Rated Load Amps (RLA 50 Hz):** 4  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 8.2  
**Motor Resistance (Ohm) - Main:** 2.94  
**Motor Resistance (Ohm) - Start:** 8.83

MotorType:  
Overload Type:

CSR

Relay Type:

Agency Approval