

TLES10KK.3 & TLY10KK.3 - key benefits

- Based on well-proven TL technology
- Extending TL-range to 128W | 156 W *
- Maintain small housing size
- High & medium efficient
- Low Noise
- Supporting our customers to comply with their energy-target

* EN12900/CECOMAF | ASHRAE



Technical data

General		TLES10KK.3	TLY10KK.3
Code number		102H4038	102H4042
Approvals		EN 60335-2-34 with Annex AA	
Application			
Application		LBP	
Evaporating temperature	°C	-35 to -10	
Voltage range/frequency	V/Hz	198 - 254/50	
Performance data (EN12900/CECOMAF ASHRAE • 220V/50Hz • RC 4µF • static cooling)			
Evaporating temperature	°C	-25	-25
Cooling capacity	watt	126 154	128 156
Power consumption	watt	118	106
Current consumption	A	0.58	0.52
COP	W/W	1.06 1.30	1.21 1.48
Dimensions			
Height	mm	A	173
		B	169
Suction connector	location/I.D. mm angle	C	6.2 15°
	material comment		Cu-plated steel Al cap
Process connector	location/I.D. mm angle	D	6.2 25°
	material comment		Cu-plated steel Al cap
Discharge connector	location/I.D. mm angle	E	5.0 21°
	material comment		Cu-plated steel Al cap
Connector tolerance	I.D. mm		±0.09, on 5.0 +0.12/+0.20

