

PART NO. ①	MODEL NUMBER	A ±3.0	B	C	D ±3.0
497-0368-00	ZH26K4E	400.2 [15.76]	374.6 [14.75]	277.1 [10.91]	235.5 [9.27]
497-0368-01	ZH15K4E	363.8 [14.32]	338.8 [13.34]	244.5 [9.63]	202.9 [7.99]
497-0368-02	ZH19/21K4E	386.4 [15.21]	360.9 [14.21]	264.4 [10.41]	222.8 [8.77]

SPECIFICATIONS	
ES NO.	DESCRIPTION
①	ESB1-159 CLEANLINESS
②	ESB1-250 IDENTIFICATION
③	ES92-155 CONVERSION-METRIC

NOTES:

① ALL TOLERANCES ±1.5 [0.06] UNLESS OTHERWISE SPECIFIED.

DUE TO ACCUMULATED ASSEMBLY TOLERANCES THE LISTED COMPONENTS MAY VARY FROM THE MOUNTING HOLES AS SHOWN BELOW:

◇ ALL FITTINGS : ±3.0 [0.12]

- ② 2. TUBE ENDS MUST BE PLUGGED.
- ③ 3. FOR MORE INFORMATION SEE PRODUCT CATALOG.
- ④ 4. MOUNTING KIT:

GROMMET DUROMETER	4 FOOT KIT
35-45	527-0116-00



COMPRESSOR WIRING DIAGRAM


THREE PHASE MOTOR WITH INTERNAL PROTECTION

USE COPPER CONDUCTORS ONLY. USE THIS EQUIPMENT ON A GROUNDING SYSTEM ONLY. USE MINIMUM 12" C WIRE FOR AMPACITY DETERMINATION. INTERNAL MOTOR PROTECTION-ALLOW TIME FOR RESET. PRIMARY SINGLE PHASE FAILURE PROTECTION IS PROVIDED. CRANKCASE HEATER, WHEN APPLIED, MUST BE CONNECTED ONLY TO ITS RATED VOLTAGE. OVERCURRENT PROTECTION DEVICE RATING AND TYPE MUST BE IN ACCORDANCE WITH REGULATORY AGENCY AND PRODUCT APPROVALS. SEE SYSTEM NAMEPLATE. TO CORRECT IMPROPER MOTOR ROTATION, SWITCH ANY TWO SUPPLY LINES.



COMPRESSOR WIRING DIAGRAM

USE COPPER CONDUCTORS ONLY. USE MINIMUM 12" C WIRE FOR AMPACITY DETERMINATION. INTERNAL MOTOR PROTECTION ALLOW TIME FOR RESET. OVERCURRENT PROTECTION DEVICE RATING AND TYPE MUST BE IN ACCORDANCE WITH REGULATORY AGENCY AND PRODUCT APPROVALS. SEE SYSTEM NAMEPLATE. CRANKCASE HEATER, WHEN APPLIED, MUST BE CONNECTED ONLY TO ITS RATED VOLTAGE. TO CORRECT IMPROPER ROTATION OF THREE PHASE MODELS, SWITCH ANY TWO SUPPLY LINES. REFER TO THE APPLICABLE SYSTEM WIRING DIAGRAM.



XX
052-1072-00

ECN	NO	REV	DESCRIPTION	DATE	BY	CHKD	APP'D
ECN000990	6	ADDED CPC		02-03-09	JYU	BG	VC
32-0906-047	5	CHANGED FORMAT FOR PROJECT INC		03-05-07	SVX	CHR	RST
32-0105-057	4	REORAIN AND REVISED		07-09-04	IMND	DC	DC
32-1001-009	0	RELEASED		10-11-01	DES	CHM	JD

10	THIS DRAWING AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF EMERSON CLIMATE TECHNOLOGIES, INC. AND SHALL BE RETURNED UPON DEMAND AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, EITHER ELECTRONICALLY OR MECHANICALLY, WITHOUT THE WRITTEN CONSENT OF EMERSON CLIMATE TECHNOLOGIES, INC.
10	CONFIDENTIALITY NOTICE

DATE	DATE FORMAT
01-08-04	MM-DD-YY
SCALE	SCALE FORMAT
3:4	MM-DD-YY
SUPERSEDES DWG. NO.	7 REV. NO.
N/A	497-0368-00 / 3
DATE	DATE FORMAT
01-08-04	MM-DD-YY
SCALE	SCALE FORMAT
3:4	MM-DD-YY
DRAWING NUMBER	SHEET 1 OF 2
497-0368-00	1 OF 2



INTERPRET PER ASME Y14.194 AND EMERSON CLIMATE TECHNOLOGIES, INC. DESIGN STANDARDS 002002-00 NOT SCALE DRAWING THIS DRAWING IS THE PROPERTY OF EMERSON CLIMATE TECHNOLOGIES, INC. UNLESS OTHERWISE SPECIFIED TOLERANCES ARE MILLIMETER OR INCH: 1-PLACE ± ANGULAR ± N/A