

Model: AJ2422X-TZ1C
Product Description

Type:	Reciprocating Compressors
Application:	LBP - Low Back Pressure
Refrigerant:	MULTI
Voltage/Frequency:	440V 3~ 60Hz 400V 3~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					

General

Evaporating Temp. Range:	-40°C to -12.2°C (-40°F to 10°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	18
Weight Unit of Measure:	KG
Displacement (cc):	15.2
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	475

Electrical

Voltage Range (50 Hz):	340-440
Voltage Range (60 Hz):	396-499
Locked Rotor Amps (LRA):	9.8
Rated Load Amps (RLA 50 Hz):	1.1
Rated Load Amps (RLA 60 Hz):	1.1
Max. Continuous Current (MCC in Amps):	2.2
Motor Resistance (Ohm) - Main:	21
Motor Resistance (Ohm) - Start:	21

MotorType:
Overload Type:

3PH

Relay Type:

[Agency Approval](#)