

**Model: RGA5510CXA**
**Product Description**

**Type:** Rotary Compressors  
**Application:** HBP/AC - Air Conditioning  
**Refrigerant:** R-407C  
**Voltage/Frequency:** 115V ~ 60Hz 100V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	115V ~ 60HZ	8652	2180	2535	911	9.5	2.39	2.78	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	100V ~ 50HZ	7038	1774	2062	745	9.45	2.38	2.77	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

**General**

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 12  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 14.25  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 53  
**Oil Charge (cc):** 290

**Electrical**

**Voltage Range (50 Hz):** 90-110  
**Voltage Range (60 Hz):** 103-127  
**Locked Rotor Amps (LRA):** 58  
**Rated Load Amps (RLA 50 Hz):** 9.2  
**Rated Load Amps (RLA 60 Hz):** 9.2  
**Max. Continuous Current (MCC in Amps):** 0

Motor Resistance (Ohm) - Main: .645  
Motor Resistance (Ohm) - Start: 4.11

MotorType: CSR

Overload Type:

Relay Type:

## Agency Approval

CE Listed, UL Recognized