

Model: AE5465C-FZ3C
Product Description

Type:	Reciprocating Compressors
Application:	HBP/AC - Air Conditioning
Refrigerant:	R-407C
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	5050	1273	1480	577	8.75	2.21	2.57	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE	240V ~ 50HZ	5050	1273	1480	615	8.21	2.07	2.41	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	11
Weight Unit of Measure:	KG
Displacement (cc):	10.33
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	386.65

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	18.5
Rated Load Amps (RLA 50 Hz):	2.88
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.95
Motor Resistance (Ohm) - Start:	12.61
Motor Type:	CSR
Overload Type:	
Relay Type:	

Agency Approval

CE Listed, VDE Listed